



SITE BACKGROUND Overview

- Collapse of the World Trade Center
 - unprecedented disaster
- Large area of dust deposition in an urban environment
- Conflicting information on asbestos usage and replacement with Zonolite









EPA Program Components (Many other non-EPA activities)

- COPC/Benchmark Report
 - Identify Contaminants of Potential Concern
- Confirmation Cleaning Study
 - Confirm effectiveness of cleanup techniques
- Background Study
 - Collect data on background levels in upper Manhattan
- WTC Dust Cleanup Program
 - Clean residential spaces upon request (apartments, common spaces, HVACs)
 - Voluntary, residential units south of Canal Street in lower Manhattan









SITE BACKGROUND Geography/Affected Area

- Dust cloud radiating out from World Trade Center (Ground Zero) through lower Manhattan
- Lower mass of dust/debris traversed the East river to Brooklyn










Regional Asbestos / Particulate Monitoring Sites Implemented In Response to the Attack on the World Trade Center





SITE BACKGROUND Populations Affected

- Disaster Response Workers
 - Emergency response workers/volunteers
 - Iron/construction workers
 - Day laborers
- Office workers
- Residents
- Visitors









SITE BACKGROUND Mineral Forms of Asbestos

- Outdoor
 - Predominately chrysotile
- Indoor
 - Predominately chrysotile (878/20,877)

Asbestos Type	Detects	Asbestos Type	Detects
Chrysotile	878	Tremolite	5
Amosite	31	Crocidolite	1
Actinolite	9	Amphibole	1
Anthophyllite	6	Combination	16



SITE BACKGROUND Asbestos-Related Health Effects

- Occupational Exposure
 - Presently none observed due to recent exposure (acute, non-asbestos effects evident)
 - Long-term uncertain due to difficulty in dose reconstruction (e.g., variable exposure times)
- Environmental Exposure
 - Outdoor none observed (acute, nonasbestos effects evident)
 - Indoor sampling data suggests minimal risk for long term health impacts









- SOIL Sampling/Analysis/Results/ Risks/Remediation
- Soil samples were not collected due to surfical deposition
- Dust that was deposited was removed by natural forces (primarily rain) or by vacuum trucks
 - Department of Sanitation (NYC)
 - NYCDEP (exterior of buildings)









ACTIVITIES BY EXPOSURE PATHWAY – DUST - Sampling

- Methods Used
 - Wipe and microvacuum (bulk other source)
 - Ultrasonification Carpet (non-EPA)
- Location of Samples
 - Non-EPA Indoor residential dwellings
 - EPA one heavily impacted building (Confirmation Cleaning) and upper Manhattan (Background study)
- Number of Samples
 - Non-EPA uncertain
 - EPA Confirmation Cleaning (156 Wipe; 124 Microvac), Background Study (146 Wipe; 161 Microvac)









ACTIVITIES BY EXPOSURE PATHWAY – DUST - Sampling (conclusion)

- Problems
 - No known problems for asbestos
 - Others mostly related to lead and dioxin sampling









ACTIVITIES BY EXPOSURE PATHWAY – DUST - Analysis

- Mineralogic Asbestos Evaluation
 - Serpentine and six common amphiboles
- Specific Counting Procedures or Rules
 - ASTM 5755 count fibers >0.5
 microns, aspect ratio 5:1
- Cleavage Fragments
 - No special rules









ACTIVITIES BY EXPOSURE PATHWAY – DUST - Analysis (cont)

- Estimated Sensitivity to Methods
 - Minimum sensitivity ~1,000 f/cm² (wipe and microvacuum methods)
 - Matrix interference often resulted in higher detection limits
- Deviations from Standard Protocols
 - None reported









ACTIVITIES BY EXPOSURE PATHWAY – DUST - Analysis (conclusion)

Issues

- Limitations on use of K-factors to evaluate risk
- Porous vs. hard surfaces
 - Interpretation of ultrasonification results
- Sample location









ACTIVITIES BY EXPOSURE PATHWAY – DUST - Results

EPA

CC = Confirmation Cleaning Study Pre = Pre-cleaning

Post = Post-cleaning

Bkg. = Background Study

	Wipe (s/cm²)		
	Min	Max	Mean
CC-Pre	<3164	10,967,100	372,097
CC-Post	<1582	888,172	55,493
Bkg.	<634	72,094	2,783
	Microvacuum (s/cm²)		
	Min	Max	Mean
CC-Pre	<2366	233,475	25,951
CC-Post	<738	197,860	14,322
Bkg.	<1184	3,798,910	37,174









ACTIVITIES BY EXPOSURE PATHWAY – DUST - Remediation Strategy

- Use standard cleaning techniques
 - Specifically, HEPA vacuuming followed by wet wiping, as per Confirmation Cleaning Study
- Recommended discarding heavily contaminated (i.e., large dust load) personal items and porous materials
- Whole building HVAC systems and common areas









ACTIVITIES BY EXPOSURE PATHWAY – AIR -Sampling (Outdoor)

- Methods Used
 - As per TEM AHERA with modification to identify fibers > 5 microns
 - As per PCM NIOSH 7400 (used to obtain total fiber counts)
- Location of Samples
 - 20 sites ringing WTC site and Freshkill Landfill
- Number of Samples
 - Over 8,000 (~40/day for 200 days)









ACTIVITIES BY EXPOSURE PATHWAY – AIR - Sampling (Indoor)

- Methods Used
 - Non-EPA standard methods
 - EPA SKC Aircheck Samplers w/ 0.8 or 0.45 micron membranes
- Location of Samples
 - One per room, minimum 3/apartment
- Number of Samples
 - Non-EPA uncertain
 - EPA Lower Manhattan Cleanup (>25,000),
 Confirmation Cleaning (171), Background
 Study (64)









ACTIVITIES BY EXPOSURE PATHWAY – AIR - Sampling (conclusion)

- Problems
 - Outdoor
 - Disaster conditions (e.g., no electricity)
 - Overloaded filters due to ambient particulate concentration
 - Indoor
 - Overloaded filters due to greater air volumes to reach lower analytical sensitivity









ACTIVITIES BY EXPOSURE PATHWAY – AIR - Analysis (Outdoor and Indoor)

- Mineralogic Asbestos Evaluation
 - Serpentine and six common amphiboles
- Specific Counting Procedures or Rules
 - EPA AHERA
 - EPA AHERA for PCMe
 - NIOSH 7400 (PCM)
- Cleavage Fragments
 - No special rules









ACTIVITIES BY EXPOSURE PATHWAY – AIR - Analysis (cont)

Estimated Sensitivity to Methods

	Outdoor	Indoor
EPA AHERA	0.005 f/cc	0.0005 f/cc
EPA AHERA (PCMe)	0.005 f/cc	0.0005 f/cc
NIOSH 7400 (PCM)	0.01 f/cc	0.001 f/cc

- Deviations from Standard Protocols
 - Volume of air









ACTIVITIES BY EXPOSURE PATHWAY – AIR - Analysis (conclusion)

Issues

- Outdoor
 - Adjust AHERA counts to standardized volume (i.e., 1200 liters)
- Indoor
 - Aggressive vs. modified-aggressive
 - Definition of overloaded filter
 - Analytical sensitivity influenced target risk level









ACTIVITIES BY EXPOSURE PATHWAY – AIR - Results

- Personal Monitors
 - OSHA monitored WTC site workers
 - OSHA issued negative exposure assessment for indoor cleanup workers
 - EPA personal monitoring during Confirmation Cleaning Study
 - Asbestos concentrations below 0.1 f/cc (OSHA PEL) [one exception]
 - EPA personal monitoring during first 10-weeks of Lower Manhattan Indoor Dust Cleanup Program
 - All below 0.1 f/cc (OSHA PEL)
- Area Sampling
 - See next panel









ACTIVITIES BY EXPOSURE PATHWAY – AIR - Estimated Risks (Outdoor)

Risks

- One-year risk-based value = 0.028 s/cc based on 10⁻⁴ risk
- AHERA standard converted to volume = 0.022 s/cc
- Eleven samples over AHERA standard of 70 s/mm²
- Criteria Used
 - Compared results to AHERA standard (70 s/mm²)










ACTIVITIES BY EXPOSURE PATHWAY -AIR - Estimated Risks (Indoor)



- Risks
 - Few above health-based benchmark
- Criteria Used
 - 30-year, risk-based benchmark of 0.0009 s/cc based on 10⁻⁴ risk





Above

Overloaded



Other Source Material Sampling

- Methods Used
 - EPA 600 R93-116 Bulk Dust
- Location of Samples
 - Perimeter of WTC-site and various locations in lower Manhattan
- Number of Samples
 - -145
 - Samples obtained by many other groups (USGS, Rutgers, Dept. of Education)









Other Source Material Sampling (conclusion)

Problems

- 1% rule does not work well for directing cleanup program
- Total mass not taken into account









Other Source Material Analysis

- Mineralogic Asbestos Evaluation
 - Serpentine and six common amphiboles
- Specific Counting Procedures or Rules
 - 400 point counting procedure
- Cleavage Fragments
 - No special rules









Other Source Material Analysis (cont)

- Estimated Sensitivity to Methods
 - 400 point counting procedure is approximately 0.25%

- Deviations from Standard Protocols
 - None reported









Other Source Material Analysis (conclusion)

- Issues
 - 1% rules not risk based; can be misleading









Other Source Material Results

- ¼ of samples (37/145) were above
 1%
- Range = Trace to 5.4%
- Sample obtained directly from steel Ibeam contained ~40%









Other Source Material Estimated Risk

- No direct extrapolation of risk
- Results used to characterize dust as potentially asbestos-containing material









Other Source Material Remediation Strategy

 Vacuum trucks equipped with HEPAfilters

 Other techniques for removing bulk debris using engineering controls to minimize dust generation









Site Remedial Actions – Actions Completed

- WTC-site officially completed in May 2002
- Confirmation Cleaning Study field work completed in October 2002; report May 2003
- Background Study field work completed in October 2002; report May 2003
- Lower Manhattan Indoor Dust Cleanup Program
 - Cleaning and testing completed July 2003
 - Final report due in October 2003







Site Remedial Actions – Ongoing Site Plans

QUESTIONS? For more detail: www.epa.gov/wtc

Asbestos Site Evaluation, Communication and Cleanup

Keystone, Colorado September 22—26, 2003





